



Označení	Typová řada	Provozní tlak v barech	Ø d1 (mm)	F1	L (mm)	S
HR 06 LU 7/16	L	PN 315	6	7/16" -20 UNF	26,0	17
HR 06 LU 1/2	L	PN 315	6	1/2" -20 UNF	26,0	17
HR 06 LU 9/16	L	PN 315	6	9/16" -18 UNF	28,0	19
HR 08 LU 7/16	L	PN 315	8	7/16" -20 UNF	29,0	17
HR 08 LU 1/2	L	PN 315	8	1/2" -20 UNF	29,0	17
HR 08 LU 9/16	L	PN 315	8	9/16" -18 UNF	30,0	19

Označení	Typová řada	Provozní tlak v barech	Ø d1 (mm)	F1	L (mm)	S
HR 10 LU 7/16	L	PN 315	10	7/16" -20 UNF	30,0	17
HR 10 LU 9/16	L	PN 315	10	9/16" -18 UNF	31,0	19
HR 10 LU 3/4	L	PN 315	10	3/4" -16 UNF	33,0	24
HR 12 LU 9/16	L	PN 315	12	9/16" -18 UNF	29,0	19
HR 12 LU 3/4	L	PN 315	12	3/4" -16 UNF	31,0	24
HR 12 LU 7/8	L	PN 315	12	7/8" -14 UNF	34,0	27
HR 15 LU 9/16	L	PN 315	15	9/16" -18 UNF	31,0	24
HR 15 LU 3/4	L	PN 315	15	3/4" -16 UNF	32,0	24
HR 15 LU 7/8	L	PN 315	15	7/8" -14 UNF	35,5	27
HR 18 LU 3/4	L	PN 315	18	3/4" -16 UNF	33,0	27
HR 18 LU 7/8	L	PN 315	18	7/8" -14 UNF	34,7	27
HR 18 LU 1 1/16	L	PN 315	18	1.1/16" -12 UN	37,0	32
HR 22 LU 7/8	L	PN 160	22	7/8" -14 UNF	37,0	32

Označení	Typová řada	Provozní tlak v barech	Ø d1 (mm)	F1	L (mm)	S
HR 22 LU 1 1/16	L	PN 160	22	1.1/16" -12 UN	39,0	32
HR 22 LU 1 5/16	L	PN 160	22	1.5/16" -12 UN	40,0	41
HR 28 LU 7/8	L	PN 160	28	7/8" -14 UNF	40,0	41
HR 28 LU 1 1/16	L	PN 160	28	1.1/16" -12 UN	40,0	41
HR 28 LU 1 5/16	L	PN 160	28	1.5/16" -12 UN	40,0	41
HR 35 LU 1 5/16	L	PN 160	35	1.5/16" -12 UN	43,0	46
HR 35 LU 1 5/8	L	PN 160	35	1.5/8" -12 UN	43,0	50
HR 35 LU 1 5/8	L	PN 160	35	1.5/8" -12 UN	45,0	55
HR 42 LU 1 7/8	L	PN 160	42	1.7/8" -12 UN	45,0	60
HR 06 SU 7/16	S	PN 630	6	7/16" -20 UNF	31,0	17
HR 08 SU 7/16	S	PN 630	8	7/16" -20 UNF	31,0	17
HR 08 SU 1/2	S	PN 630	8	1/2" -20 UNF	31,0	19

Označení	Typová řada	Provozní tlak v barech	Ø d1 (mm)	F1	L (mm)	S
HR 08 SU 9/16	S	PN 630	8	9/16" -18 UNF	32,0	19
HR 10 SU 9/16	S	PN 630	10	9/16" -18 UNF	32,0	19
HR 10 SU 3/4	S	PN 630	10	3/4" -16 UNF	33,0	24
HR 12 SU 9/16	S	PN 630	12	9/16" -18 UNF	32,0	22
HR 12 SU 3/4	S	PN 630	12	3/4" -16 UNF	36,0	24
HR 12 SU 7/8	S	PN 630	12	7/8" -14 UNF	38,0	27
HR 14 SU 3/4	S	PN 630	14	3/4" -16 UNF	35,0	24
HR 16 SU 3/4	S	PN 400	16	3/4" -16 UNF	35,0	24
HR 16 SU 7/8	S	PN 400	16	7/8" -14 UNF	40,0	27
HR 16 SU 1 1/16	S	PN 400	16	1.1/16" -12 UN	44,0	32
HR 20 SU 3/4	S	PN 400	20	3/4" -16 UNF	42,0	32
HR 20 SU 7/8	S	PN 400	20	7/8" -14 UNF	44,0	32
HR 20 SU 1 1/16	S	PN 400	20	1.1/16" -12 UN	46,0	32

Označení	Typová řada	Provozní tlak v barech	Ø d1 (mm)	F1	L (mm)	S
HR 25 SU 1 1/16	S	PN 400	25	1.1/16" -12 UN	50,0	41
HR 25 SU 1 5/16	S	PN 400	25	1.5/16" -12 UN	50,0	41
HR 30SU 1 5/16	S	PN 400	30	1.5/16" -12 UN	52,0	46
HR 30SU 1 5/8	S	PN 400	30	1.5/8" -12 UN	52,0	50
HR 38SU 1 5/8	S	PN 315	38	1.5/8" -12 UN	57,0	55
HR 38SU 1 7/8	S	PN 315	38	1.7/8" -12 UN	57,0	60

typová řada:

LL = velmi lehká L = lehká S = robustní - PN = nominální tlak PB = max. provozní tlak - Ø d2 = vnější průměr trubky