



NORTH FIGHTER® TWIN 2SC

High-quality, very flexible hydraulic hose with a single steel braid, exceeding EN 857 2SC standard requirements.



TECHNICAL SPECIFICATION

- Recommended for medium pressure applications
- Exceeds EN 857 2SC standard
- Outer cover resistant to oils and weather conditions
- Impulse tested for a minimum of 200,000 cycles

								
	Size (inch)	Inner Diameter (mm)	Outer Diameter (mm)	Total Width (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)
TWIN 2SC 06	1/4"	6.2 - 6.6	13.1 ±0.3	26.8 ±0.5	400	1600	75	0.57
TWIN 2SC 08	5/16"	7.7 - 8.1	15.0 ±0.3	30.6 ±0.5	350	1400	85	0.67
TWIN 2SC 10	3/8"	9.3 - 9.7	17.1 ±0.3	34.8 ±0.5	330	1320	90	0.80
TWIN 2SC 12	1/2"	12.5 - 12.9	20.6 ±0.3	41.8 ±0.5	275	1100	130	0.96
TWIN 2SC 16	5/8"	15.7 - 16.1	24.0 ±0.3	48.6 ±0.5	250	1000	170	1.11



RESISTANT AGAINST:
MINERAL AND HYDRAULIC OILS



TUBE:
SYNTHETIC RUBBER



REINFORCEMENT:
DOUBLE STEEL BRAID



COVER:
SYNTHETIC RUBBER



TEMPERATURE RANGE:
-40°C - 120°C



NORMS:
DIN EN 857 2SC, ISO 11237



SAFETY FACTOR:
4:1