



TECHNICAL SPECIFICATION

- Recommended for medium pressure applications
- Exceeds EN 857 1SC standard
- Outer cover resistant to oils and weather conditions
- Impulse tested for a minimum of 150,000 cycles

								
	Size (inch)	Inner Diameter (mm)	Outer Diameter (mm)	Total Width (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)
TWIN 1SC 06	1/4"	6.2 - 6.6	12.2 ±0.3	25.0 ±0.5	225	900	50	0.39
TWIN 1SC 08	5/16"	7.7 - 8.1	13.7 ±0.3	28.0 ±0.5	215	860	55	0.45
TWIN 1SC 10	3/8"	9.3 - 9.7	15.7 ±0.3	32.0 ±0.5	180	720	63	0.54



RESISTANT AGAINST:
MINERAL AND HYDRAULIC OILS



TUBE:
SYNTHETIC RUBBER



REINFORCEMENT:
SINGLE STEEL BRAID



COVER:
SYNTHETIC RUBBER



TEMPERATURE RANGE:
-40°C - 120°C



NORMS:
DIN EN 857 1SC, ISO 11237



SAFETY FACTOR:
4:1